



\$55,500.00

Versatility  
Performance  
Reliability

# LV520S

## Bag Styles



## Optional Weighers



## Auxiliary Equipment



**BPI Equipment Inc.**

USA 574-307-1274

sales@bpiequip.com

www.bpiequip.com



VPB522B/555001A8500



## General Information

**Maximum Speed:**  
Up to 80 Bags/Min

**Minimum Bag Size:**  
50mm(W) x 50mm(L)  
1.96" (W) x 1.96" (L)

**Maximum Bag Size:**  
250mm(W) x 350mm(L)  
9.84" (W) x 13.78" (L)

**Maximum Web Width:**  
120mm-520mm | 4.72"-20.47"

**Film Thickness:**  
0.04mm - 0.09mm

**Standard Electrical:**  
220v/20amp Single Phase/3  
Phase Depending on Options

**Equipment Dimension's:**  
1560mm x 1160mm x 1530mm  
61.4" (L) x 45.7" (W) x 60.2" (H)

**Weight:** 480Kg | 1058Lbs

## Technical Advantages

- High speeds without the high maintenance
- Designed with 90% less air components
- Servo motor drive film pull system
- Smooth servo drive seal jaw actuation
- Auto electric rectifying film tracking system
- Electric photo eye film registration
- Siemens control platform & components
- Smooth and quiet operational system
- Runs most common film structures
- Auto stop end of film lock down device
- Quick change film splice table
- VFD powered film unwind for high accuracy
- Minimal maintenance with easy operations
- Off the shelf components on most wear parts

## Options

- Ethernet remote diagnostics
- Side gusset bag device
- Gas flush assembly
- Round/Euro hole punch
- Tear notch device
- Static eliminator devices
- Vacuum pull belts and pump
- Load shelf assembly
- Chain bag repeat controls
- In-feed and exit conveyors
- Integration with variety of fillers, weighers, printers and metal detectors

